



USB to 4 Isolated Inputs Digital Interface Adapter

Part: 8113 | **Model:** SeaDAC Lite ISO-4

Control and monitor four optically isolated inputs via any USB connection with the 8113. Inputs can range from 5-30VDC and provide 3500VDC (2500VAC RMS) isolation to ground. Status LEDs display I/O activity and field wiring is simplified via 3.5mm removable terminal blocks.

The SeaMAX software suite supports the SeaDAC Lite family and is designed to work with third party applications via the SeaMAX API. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Windows and Linux operating systems.

The 8113 integrates Sealevel's SeaLATCH locking USB port, which is fully compatible with standard USB cables. When used with the included USB cable with a SeaLATCH USB type B connector, the metal thumbscrew provides a secure connection to the device and prevents accidental cable disconnection.

SeaDAC Lite modules are housed in a rugged, attractive plastic enclosure ideal for mounting on walls, under counters, or inside panels. The 8113 is USB bus powered, so no external power supply is needed. Standard operating temperature range of SeaDAC modules is 0C to +70C and extended temperature range (-40C to +85C) is optional.

Features & Specifications

USB to 4 Isolated Inputs Digital Interface Adapter

Part: 8113 | **Model:** SeaDAC Lite ISO-4

Features

- 4 optically isolated inputs
- Optical isolation provides protection against surges and ground loops
- Field wiring is simplified via removable 3.5mm terminal blocks compatible with 16-30 AWG wire
- Optional removable spring-clamp terminal blocks available
- Status LEDs display serial transmit and receive activity
- Sealevel's SeaLATCH locking USB port provides secure connection with SeaLATCH USB cables via metal thumbscrews
- Powered by USB connection
- Sealevel software supports Windows 7/Vista/XP/2000 operating systems
- Housed in rugged, attractive plastic enclosure
- Includes 6' USB type A to SeaLATCH USB type B device cable (Item# CA356)

Specifications

Family	SeaDAC Lite
Digital I/O	Isolated Inputs
Dimensions	4.3 (L) x 3.4 (W) x 1.3 (H)
Extended Temperature	Call for Options
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Input Isolation	2500VAC RMS, 3500VDC
Input Range	5-30 VDC
Input Impedance	6.2K Ohms (in series)
Host Interface(s)	USB
Number of Inputs/Outputs	4 inputs
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	4
Power Requirement	+5V @ 500mA
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
USB Specification	1.1 Compliant, 2.0 Compatible