

SealSO Single Port Inline USB Isolator (UL Recognized)

Part: ISO-1 Model: SealSO USB Isolator

The SealSO™ ISO-1 single-port, inline USB isolator offers a simple method of protecting host and field equipment from damaging transients and surges commonly found in commercial, industrial and medical environments. The ISO-1 is UL Recognized, in accordance with EN60601-1 3rd Edition, and protects both the data and power lines with 4 kV of medical-grade isolation between the host control system and connected USB equipment.



The ISO-1 is USB bus powered, eliminating the need for external power. The efficient DC/DC design allows energy transfer over the isolation barrier. The isolator provides up to 300 mA to a downstream USB device when connected to a standard 500 mA USB port. Additionally, the isolator can provide a full 500 mA to a downstream device when connected to a USB port capable of sourcing 1 A, or greater. Convenient high-retention USB connectors prevent accidental cable disconnections.

Supported in Microsoft Windows, Linux, and other USB aware operating systems, the ISO-1 requires no separate drivers and is easy to install. Simply plug the isolator into an available USB port with the included cable, and it is automatically recognized as a generic USB hub device. The ISO-1 is a USB 2.0 compatible device connecting to the host over a high-speed link and features full-speed (12 Mbps) data rates between the downstream USB device.

The ISO-1 is housed in a rugged plastic enclosure with mounting ears that simplify mounting to walls, under counters, or inside panels. Standard operating temperature range is -20°C to 60°C and extended temperature ranges are optional. The USB isolator is shipped with a 1 meter USB A to B device cable and 1.3 meter USB extension cable. If you need a ruggedized USB isolator cable, see the ISO-1R. If you need an OEM USB isolator to integrate into your application, see the ISO-1-OEM.

Features

- Protects host and field equipment from damaging surges and transients
- UL Recognized in accordance with EN60601-1 3rd Edition requirements
- Features medical-grade 4 kV isolation, data, and power
- Powered by USB host connection; supports energy transfer with isolation
- Maximum of 1.1 A output current when connected to a high-power USB port
- Provides 300 mA to downstream USB devices when connected to standard 500 mA USB port
- Provides 500 mA to downstream USB devices when connected to 1 A USB port
- High-retention USB connectors prevent accidental disconnection of USB cable
- USB 2.0 compatible device supports full-speed 12 Mbps operation
- Includes 1 meter USB type A to type B device cable (Item# CA539)
- Includes 1.3 meter USB type A male to USB type A high-retention female extension cable (Item# CA536)
- Compliant with CE, FCC, RoHS and WEEE directives



**Design & Manufacturing
Experience**

**Long-term Availability
Guaranteed**

Lifetime Warranty

SealSO Single Port Inline USB Isolator (UL Recognized)

Part: ISO-1 Model: SealSO USB Isolator

Specifications

Family

- SealSO

Certifications

- EN60601-1 3rd Edition, FCC, CE

Communications Chip

- USB Hub

Dimensions

- Enclosure: 7.6" (L) x 2.0" (W) x 1.1" (H) – 4.0" (L) w/o Mounting Ears

Humidity Range

- 10 – 90% Relative Humidity, Non-Condensing

Host Interface(s)

- USB

Max Data Distance

- 5 M

Max Data Rate

- 12 Mbps (Device Connection)

Operating Temperature

- -20°C to 60°C (-4°F to 140°F)

of Ports

- 1

Power Requirement

- USB +5V @ 200 mA (Max)

RoHS Compliant

- Yes

Storage Temperature

- -40°C to 85°C (-40°F to 185°F)

Upstream Isolation

- 4 kV Isolation

USB Specification

- 2.0 Compatible (Host Connection)

