



Ethernet to 4 Form C Relay Outputs Digital Interface Adapter

Part: 150E | **Model:** eI/O REL-4C

Control and monitor four high-current Form C relay outputs via any 10/100BaseT Ethernet connection with the eI/O-150E digital I/O module. The Form C relays can switch up to 6A loads at 200VAC and up to 5A at 60VDC. Each Form C relay has a discrete common and includes normally-open and normally-closed contact connections for easy field wiring via removable 3.5mm terminal blocks.

The eI/O-150E receives power via a removable spring-clamp terminal block. The lever-style clamping mechanism requires no tools, which simplifies field installation. The module is powered by your 9-30VDC source, or select from a variety of Sealevel power supply options.

Ready for DIN rail mounting, the eI/O-150E includes a removable plastic clip that snaps onto 35mm DIN rail. The clip can also be attached to any flat surface such as a wall or under a counter. Standard operating temperature range of eI/O Ethernet digital I/O modules is 0C to +70C. Status LEDs on the front show power and I/O activity. Additionally, LEDs on the RJ45 connector display Ethernet link and communication activity.

Communicate with eI/O Ethernet digital I/O modules using industry standard Modbus TCP protocol or use the Sealevel SeaMAX API software libraries from your application program. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows operating systems.

The Sealevel Modbus Connect app for iOS allows you to access the registers, coils and discrete I/O of your Sealevel Modbus devices and is available on the App Store. Use the app to remotely access I/O in the field or for testing and troubleshooting during application development. The Sealevel Mod+ Connect app is an easy-to-use diagnostic utility that allows you to monitor, test and troubleshoot Sealevel eI/O and Seal/O modules using your iPhone or iPod touch.

Features & Specifications

Ethernet to 4 Form C Relay Outputs Digital Interface Adapter

Part: 150E | **Model:** eI/O REL-4C

Features

- 10/100BaseT Ethernet Modbus TCP interface
- 4 high-current SPDT Form C relays can switch up to 5A at 60VDC
- Field wiring is simplified via removable 3.5mm terminal blocks compatible with 16-30 AWG wire
- Ready for DIN rail mounting, removable plastic clip snaps onto 35mm DIN rail or can be attached to walls and other surfaces with optional screws
- Optional removable spring-clamp terminal blocks available for I/O connections
- Input power via removable spring-clamp terminal block
- Status LEDs display power, Ethernet link and I/O activity
- Sealevel SeaMAX software supports Microsoft Windows operating systems
- Housed in rugged, attractive plastic enclosure
- Includes 7' CAT5 Ethernet cable (Item# CA246)

Specifications

Family	eI/O
Field Wiring	16 – 30 AWG
Contact Current DC	≤ 30 VDC @ 5A max. > 30 VDC @ 2000mA max., (100mA min.)
Contact Operate Time	10ms max.
Contact Release Time	5ms max.
Contact Voltage	60VDC max., 200VAC max., (5VDC min.)
Digital I/O	Form C Relay Outputs
Dimensions	4.5 (L) x 3.5 (W) x 1.3 (H)
Contact Current AC	6A max.
Host Interface(s)	Ethernet
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Operating Temperature	0°C to 70°C (32°F to 158°F)
Output Power	DC 240W, AC 300 VA
Output Type	SPDT Form C relays
# of Ports	4
Power Requirement	9-30 VDC @ 5W
RoHS Compliant	Yes
Storage Temperature	-50°C to 105°C (-58°F to 221°F)