



# PCI 2-Port RS-232 Serial Interface

**Part:** 7202 | **Model:** COMM+232.PCI

The 7202 PCI serial interface provides two RS-232 serial ports capable of data rates to 460.8K bps. Each RS-232 port implements all modem control signals for maximum compatibility with a wide range of peripherals. The 7202 utilizes 16C850 UARTs that provide 128-byte Tx/Rx FIFOs.

Sealevel's SeaCOM software makes installation and operation easy using Microsoft Windows and Linux operating systems.

## Features & Specifications

### PCI 2-Port RS-232 Serial Interface

Part: 7202 | Model: COMM+232.PCI

#### Features

- 16C850 buffered UARTs with 128-byte FIFOs
- Data rates to 460.8K bps
- All modem control signals implemented
- Two DB-9M connectors

#### Specifications

<b>Communications Chip</b>	16C850
<b>Electrical Interface</b>	RS-232
<b>Humidity Range</b>	10 – 90% Relative Humidity, Non-Condensing
<b>Host Interface(s)</b>	PCI
<b>Max Data Distance</b>	50 feet
<b>Max Data Rate</b>	460.8K bps
<b>Operating Temperature</b>	0°C to 70°C (32°F to 158°F)
<b>PC Bracket</b>	Standard Height
<b># of Ports</b>	2
<b>Serial Connector(s)</b>	DB9M
<b>Storage Temperature</b>	-50°C to 105°C (-58°F to 221°F)
<b>UART Series</b>	850 UART